

AMEDDC&S HRCOE PAM 350-10

| EFMB Test Score Sheet WARRIOR SKILLS — DISASSEMBLE, ASSEMBLE, AND PERFORM A FUNCTIONS CHECK ON AN M17/M18 PISTOL (For use of this form, see AMEDDC&S HRCoe Pam 350-10, the proponent is ATMC-OPE) | | |
|---|-------------|-------|
| CANDIDATE'S RANK AND NAME | CANDIDATE # | |
| TASK: DISASSEMBLE, ASSEMBLE, AND PERFORM A FUNCTIONS CHECK ON AN M17/M18 PISTOL. | | |
| CONDITIONS: Given an M17/M18 pistol and a magazine. | | |
| STANDARDS: Correctly clear and disassemble the M17/M18 pistol, matching the parts with the correct nomenclature labels within 30 seconds. Correctly assemble and perform a functions check on the M17/M18 pistol within 45 seconds. All tasks will be performed in sequence. | | |
| NOTE: THIS TASK HAS BEEN MODIFIED FOR EFMB TESTING PURPOSES ONLY. | | |
| PERFORMANCE STEPS/MEASURES | GO | NO-GO |
| 1. Unload and clear the M17/M18 pistol. | | |
| NOTE: Time begins when candidate touches the pistol. | | |
| NOTE: The lever will initially be set in the "FIRE" position and an empty magazine will be in the pistol. Keep weapon pointed in a safe direction at all times during this task. | | |
| a. Point the pistol in a safe direction for the duration of the event | | |
| b. Place the safety lever in the safe (up) position | | |
| c. Depress the magazine release and remove the magazine from the pistol. | | |
| d. Grasp the slide serrations and fully retract the slide. | | |
| e. Lock the slide to the rear using the slide stop. | | |
| f. Visually inspect the chamber, magazine well, and bolt face to ensure it is clear. Release the slide forward. | | |
| 2. Disassemble the weapon into the following components, ensuring all parts are on the correct nomenclature labels: | | |
| a. Magazine | | |
| b. Receiver | | |
| c. Barrel | | |
| d. Slide assembly | | |
| e. Recoil spring guide assembly | | |
| NOTE: Time will stop when the candidate returns to the standing position with all parts of the weapon on the flat surface. | | |
| 3. Assemble the M17/M18 pistol. | | |
| a. Grasp the slide with the bottom facing up. | | |
| b. Grasp the barrel assembly with the locking block facing up with the other hand. | | |
| c. Insert the muzzle into the forward end of the slide and simultaneously, lower the rear of the barrel assembly by moving the barrel slightly. | | |
| d. Insert the recoil spring guide into the recoil spring. | | |
| e. Insert the end of the recoil spring and the recoil spring guide into the recoil spring housing and simultaneously, compress the recoil spring and lower the spring guide until it is fully seated on the locking block cutaway. | | |
| f. Push the firing pin block lever down. | | |
| g. Grasp the slide and barrel assembly with the sights up and align the slide on the receiver assembly guide rails. | | |
| h. Push until the rear of the slide is a short distance beyond the rear of the receiver assembly and hold, simultaneously, rotate the disassembly latch lever upward. | | |

| | | | | |
|--|---|--|-----|----|
| NOTE: A click indicates a positive lock. | | | | |
| 4. Perform safety/function check. | | | | |
| NOTE: Candidate will start from the last position in the previous task. | | | | |
| a. Insert empty magazine into magazine well. Magazine catch must lock magazine in place. | | | | |
| b. Push up on manual safety lever to engage safety. | | | | |
| c. Grasp slide serrations and pull the slide to rear until it locks. The magazine follower should push up on slide stop, locking slide to rear. Press the magazine catch. The magazine will fall free from pistol. | | | | |
| d. Press the slide catch. This will release the slide to the forward position. Ensure the slide is fully forward on the pistol. | | | | |
| e. Press the trigger. The striker should not be released. | | | | |
| f. Depress manual safety lever. | | | | |
| g. Press trigger and hold to rear. Striker should be released. An audible click should be heard. | | | | |
| h. While still holding trigger to rear, fully retract and release slide. | | | | |
| i. Release trigger. A light audible click should be heard and felt as the striker resets. | | | | |
| j. Press trigger. The striker should release and you should hear and feel a loud audible click. | | | | |
| 5. Correctly perform performance steps/measures 1 and 2 within 30 seconds. | | | | |
| 6. Correctly perform performance steps/measures 3 and 4 within 45 seconds. | | | | |
| NOTE: Time will stop when the candidate returns to the standing position with the weapon on the flat surface. | | | | |
| 7. Met all administrative requirements for this task. | | | | |
| EVALUATOR WRITES: CANDIDATE'S TIME FOR 1 AND 2: | | FOR 3 AND 4: | | |
| REASON(S) FOR FAILURE | DOES THE CANDIDATE WISH TO REBUT THIS TASK? (CANDIDATE INITIALS APPROPRIATE BOX) | <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:50%; text-align: center;">YES</td> <td style="width:50%; text-align: center;">NO</td> </tr> </table> | YES | NO |
| YES | NO | | | |
| | | | | |
| LANE OIC/NCOIC INITIALS | EVALUATOR'S SIGNATURE | DATE | | |