



## DELL EMC SD-WAN SOLUTION POWERED BY VMWARE – EDGE 3000 SERIES

Next generation Dell Technologies edge networking appliances factory-integrated with VMware SD-WAN software for turnkey WAN modernization. The 3000 series is ideal for data center or central office locations, complementing the 600 series for

Dell EMC SD-WAN Solution powered by VMware combines next generation networking appliances from Dell Technologies with leading SD-WAN software from VMware. The SD-WAN Edge3000 series is a performance-designed appliance well suited for the Service Provider edge, Enterprise locations, and core data centers. The SD-WAN EDGE 3000 is 1 RU sized, using the latest Intel® Xeon® D-2100 x86-based processor which is optimized for high-performance networking. Dell Technologies is the first to market with Xeon-D for SD-WAN.

The Edge 3000 series is part of the Dell EMC SD-WAN Solution powered by VMware, which delivers:

- **Simplicity & Agility** with a Dell Technologies hardware and VMware software in one solution for turnkey modernization
- **Performance & Efficiency** that boosts applications performance and can help reduce WAN costs by up to 75%
- **Scale & Trust** by backing your modernization with enterprise-class support, services, and supply chain capabilities all from a single trusted vendor – Dell Technologies

**Purpose-built for appliance for SD-WAN** = The SD-WAN 3000 is perfect for the service provider edge or larger enterprise branch, where high-performance, modular expansion port availability, 1RU racking, and large number of configuration options are design considerations.

- Appliance integrated with VMware SD-WAN software, provides simplified ordering and reduce deployment risks
- First to market with networking optimized Intel® Xeon® D-2100 x86-based processor
- Accelerates packet processing with Intel® Data Plane Development Kit (DPDK)
- Accelerates security encryption with Intel® QuickAssist Technology (QAT)
- IO to PSU airflow, front facing ports, and redundant power option
- Short-depth chassis design excellent for telco use cases
- Processing: 8 or 16 core options
- Memory from 32GB
- Storage from 240GB
- Ports: 6X1G (standard), 4X10G SFP+
- One expansion slot is pre-populated; and one additional expansion slot is available for future capabilities

## Maximum efficiency

SD-WAN Edge 3000 enables rapid modernization of the WAN without disruptive and costly upgrades. The SD-WAN Edge 3000 is designed with headroom to scale when WAN traffic is added. Software licensing options can be upgraded to accommodate changing business requirements for features, duration, and/or bandwidth.

Adapting to change quickly provides operational efficiency.

- Scale deployment of new sites, links and network services leveraging zero-touch provisioning to bring up sites quickly including built-in firewall and easy integration with partners' firewalls.
- Centralize monitoring and management to quickly identify and troubleshoot security and network issues.
- Leverage dynamic multi-path bandwidth optimization based on app performance requirements to steer traffic around poor links and networks.

Improving availability furthers operational efficiency by transforming inexpensive broadband links into a secure enterprise-grade, secure SD-WAN improving the performance of existing connections, saving money, and improving scalability and quality of experience.

## The Dell Advantage

As part of the Dell EMC SD-WAN Solution, the SD-WAN Edge 3000 is backed by a full range of ProSupport, services, and world-class supply chain from a single trusted vendor- Dell Technologies.

## SD-WAN EDGE 3000 models

	SD-WAN Edge 3400	SD-WAN Edge 3800
CPU	Intel Xeon D-2100, 8 Core	Intel Xeon D-2100, 16 Core
Drive	240GB in standard configuration	240GB in standard configuration
RAM	32GB in standard configuration	32GB in standard configuration
Ports	(6 x 1G) + (4 x 10G SFP+)	(6 x 1G) + (4 x 10G SFP+)
Fan	4	5

## Performance and scale

	SD-WAN Edge 3400	SD-WAN Edge 3800
<b>Max Recommend Subscription</b>	<b>5 Gbps</b>	<b>10 Gbps</b>
<b>Max throughput (1300 bytes)</b>	<b>7 Gbps</b>	<b>10 Gbps</b>
<b>Average iMix Throughput</b>	<b>2.5 Gbps</b>	<b>5 Gbps</b>
<b>Max Flows per second</b>	<b>38,400</b>	<b>38,400</b>
<b>Maximum Tunnels</b>	<b>4000</b>	<b>6000</b>
<b>Maximum concurrent flows</b>	<b>3.8M</b>	<b>3.8M</b>
<b>Maximum segments</b>	<b>16</b>	<b>16</b>
<b>Maximum routes</b>	<b>100K</b>	<b>100K</b>

## VMware SD-WAN software features

Category	Features
<b>AAA</b>	RADIUS, local authentication and authorization, multitenant 3 Tier role-based access control (RBAC) architecture, auditing, roles and privileges
<b>Availability</b>	High availability for VMware SD-WAN Edge, disaster recovery for VMware SD-WAN Orchestrator, multilink for high availability of WAN, VMware SD-WAN Edge clustering
<b>Configuration and monitoring</b>	REST API, SDK (Java and Python), Syslog, SNMP, NetFlow, 3000+ applications/categories, ANPM, application usage, device identification, live mode, zero IT touch activation
<b>Deployment flexibility</b>	Eliminate pre-stage, no CLI, group policies, consolidated ICOM and end customer dashboard, VNF form-factor, multitenant stateless headend, transport group for business policy abstraction, application-aware service insertion on premises or in cloud, RMA workflow, customized application maps
<b>DMPO</b>	Application and network condition aware sub-second steering, jitter/loss correction, fast intelligent routing, intelligent gateway selection, link aggregation, TCP flow optimization, uni-directional link measurements, bandwidth detection
<b>Multitenancy</b>	VMware SD-WAN Controller, VMware SD-WAN Gateway, VMware SD-WAN Orchestrator
<b>Network Services</b>	IPv4, DNS, DHCP client, DHCP server, DHCP relay, NAT

<b>QoS</b>	Shaping, policing, per-flow queueing, tunnel shaper, multi-source inbound QoS, rate-limiter, COS aware, outer/inner DSCP tagging, smart defaults, MPLS COS
<b>Remote Troubleshooting</b>	Live mode, alerts, events, remote diagnostics (examples: DNS test, ping test, flush active flows, list active flows, paths, VPN tests, packet capture, etc.), PKI infrastructure with certificate management workflows, diagnostic bundles
<b>Routing</b>	OSPF, BGP, static, connected, ICMP probes/responders, overlay flow control, per-packet application aware steering, route filter, route redistribution
<b>SaaS/IaaS</b>	Improved performance for cloud apps, supports well-known IaaS (e.g., AWS, Azure, GCP), Cloud Web Security (e.g., Check Point, Zscaler, Palo Alto Networks, Netskope, Menlo Security, Websense, OpenDNS)
<b>Security</b>	AES256/128, SHA1/SHA2, IKEv2, VPNC compliant IPSec, PKI, segmentation, TLS1.2, SCEP, firewall L2-7, 1:1 NAT, port forwarding, dynamic branch to branch, MAC filtering security service Insertion capabilities: simplified service insertion of third-party NGFW VNF running locally on Edge simplified cloud-based NGFW, AV, IPS/IDS, threat-detection service insertion
<b>VLAN Tagging</b>	802.1Q, 802.1ad, QinQ (0x8100), QinQ (0x9100), native
<b>WAN overlay support</b>	Public/private/hybrid transport, cloud and on-premises

## Technical Specifications

<b>Overview</b>	
<b>CPU</b>	Intel Xeon-D 2100 8 cores: SD-WAN Edge 3400 16 cores: SD-WAN Edge 3800
<b>Networking ports</b>	6 x 1GE 4 x 10GE, SFP+ (using interfaces from expansion slot)
<b>Management ports</b>	2X - 10/100/1000Base-T: one for CPU and one for BMC
<b>USB ports</b>	2X - USB type A receptacle (female) ports supports USB 3.0 1X – Micro USB type B receptacle (female) port, available for console port
<b>Console ports</b>	2X – Serial: one for CPU and one for BMC
<b>Storage Option</b>	2x M.2 SATA (240GB in standard configuration, upgradable to 1.92TB with custom upgrade)
<b>Out of Band Management</b>	BMC IPMI 2.0 compliant
<b>Memory</b>	4 DIMM slot (32GB in standard configuration, upgradable to 128GB)
<b>TPM</b>	2.0
<b>QAT</b>	Yes
<b>Expansion slots</b>	1 X expansion slot available for future capabilities
<b>BMC</b>	IPMI 2.0 compliant
<b>Power Supplies</b>	Standard configuration: 16 core (2 PSU), 8 core (2 PSU)
<b>Fans</b>	Standard configuration: 16 core (5 fans), 8 core (4 fans)
<b>Airflow</b>	Air flows from I/O side to PSU side
<b>Software</b>	VMware SD-WAN software

Operations	
Operating Temperature	0°C to 45°C (32°F to 113°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Operating Relative humidity	5% to 85% (RH), non-condensing Continuously 5% to 90% (RH), non-condensing Short term (< 1% of operational hour per year)
Storage Relative humidity	5% to 90% (RH)
Operating Altitude	No performance degradation to 10,000 feet (3,048 meters)

Power	
Power Input	AC: 100 to 240 VAC, 50/60 Hz
Power consumption	SD-WAN Edge 3400 <ul style="list-style-type: none"> <li>a. Power consumption: 242W/ 178W (max/typical)</li> <li>b. Typical current: 1.62 A (110 VAC); 0.75A (240 VAC)</li> </ul> SD-WAN Edge 3800 <ul style="list-style-type: none"> <li>a. Power consumption: 312W/208W (max/typical)</li> <li>b. Typical current: 1.89A (110VAC); 0.87A (240 VAC)</li> </ul>

Physicals		Inches	cm
Product	Width	17.1	43.4
	Depth	15	38.1
	Height	1.72	4.37
Shipping Box	Width	22.64	57.5
	Depth	23.78	60.4
	Height	8.38	21.3
Rack clearance required (Front)		5	12.7
Rack clearance required (Rear)		5	12.7
Product Weight		SD-WAN 3400: 16.6 lbs (7.53kg) SD-WAN 3800: 16.5 lbs (7.48kg)	

Regulatory	
Safety	<ul style="list-style-type: none"> <li>• UL/CSA 60950-1, Second Edition</li> <li>• EN 60950-1, Second Edition</li> <li>• IEC 60950-1, Second Edition Including all National Deviations and Group Differences</li> <li>• IEC 62368-1</li> <li>• EN 60825-1 Safety of Laser Products Part 1: Equipment Classification Requirements and User's Guide</li> <li>• EN 60825-2 Safety of Laser Products Part 2: Safety of Optical Fiber Communication Systems FDA Regulation</li> <li>• 21 CFR 1040.10 and 1040.11</li> </ul>
Emissions	<ul style="list-style-type: none"> <li>• Australia/New Zealand: AS/NZS CISPR 32, Class A</li> <li>• Canada: ICES-3/NMB-3, Class A</li> <li>• Europe: EN 55024 (CISPR 24), Class A</li> <li>• Japan: VCCI Class A</li> <li>• USA: FCC CFR 47 Part 15, Subpart B, Class A</li> </ul>
Immunity	<ul style="list-style-type: none"> <li>• EN 300 386 EMC for Network Equipment</li> <li>• EN 55024</li> <li>• EN 61000-3-2: Harmonic Current Emissions</li> <li>• EN 61000-3-3: Voltage Fluctuations and Flicker</li> <li>• EN 61000-4-2: ESD</li> <li>• EN 61000-4-3: Radiated Immunity</li> <li>• EN 61000-4-4: EFT</li> <li>• EN 61000-4-5: Surge</li> <li>• EN 61000-4-6: Low Frequency Conducted Immunity</li> </ul>
RoHS	<ul style="list-style-type: none"> <li>• EN 50581:2012 All S9999 components are EU RoHS compliant.</li> </ul>

## Learn more

Dell EMC SD-WAN Solution powered by VMware enables turnkey modernization by combining Dell Technologies Edge networking appliances with VMware SD-WAN software in one solution. Our product team is proud to bring you the Edge 3000 series, designed exclusively to meet and exceed the demands for high-performance virtualized networking.

Contact your Dell Sales Representative for additional information and to discuss your next generation access requirements. For information, please visit [DellTechnologies.com/SD-WAN](https://DellTechnologies.com/SD-WAN).