

The regulation forecast is subject to change daily as actual events occur.
 Forecasted release reductions or increases are subject to change based on forecasted temperature and river conditions
 and releases may be adjusted during winter freeze-in period. Intrasystem regulation may also require release adjustments.

REGULATION FORECAST: 03/03/23

		FTPK				GARR				OAHE				BEND				FTRA				GAPT				SYSTEM				
		24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	24EL	24ID	24OD	24GE	GE	SG	DSG		
T	2	2218.6	5.6	6.5	1.74	1825.5	12.4	23.5	6.30	1594.2	26.4	14.0	3.95	1420.7	13.9	17.0	1.90	1350.2	20.0	8.5	1.80	1206.7	13.1	12.0	1.15	16.84	46063	27	2	T
F	3	2218.6	6.0	6.5	1.74	1825.4	12.8	23.5	6.30	1594.3	26.8	14.0	3.95	1420.6	14.0	17.0	1.90	1350.5	20.0	8.5	1.80	1206.7	12.3	12.0	1.15	16.84	46082	19	3	F
	4	2218.6	6.0	5.5	1.48	1825.3	13.0	22.5	6.04	1594.4	27.1	12.0	3.40	1420.8	12.4	6.0	0.69	1350.6	12.2	8.5	1.80	1206.7	12.1	12.0	1.15	14.55	46114	32	4	
	5	2218.6	6.0	5.5	1.48	1825.2	13.2	21.5	5.78	1594.5	27.0	10.0	2.84	1421.0	10.4	4.0	0.46	1350.6	8.6	8.5	1.80	1206.7	11.9	12.0	1.15	13.51	46145	31	5	
M	6	2218.6	6.0	5.0	1.35	1825.2	13.3	20.5	5.52	1594.6	26.4	16.0	4.52	1420.9	14.8	19.0	2.12	1350.8	17.6	8.5	1.80	1206.7	11.9	12.0	1.15	16.45	46160	15	6	M
T	7	2218.6	6.0	5.0	1.35	1825.1	13.3	19.5	5.25	1594.7	25.6	16.0	4.52	1420.8	16.0	19.0	2.12	1351.1	20.4	8.5	1.81	1206.7	11.9	12.0	1.15	16.19	46185	25	7	T
W	8	2218.6	6.0	5.0	1.35	1825.1	13.3	18.5	4.99	1594.7	24.8	16.0	4.52	1420.7	16.0	19.0	2.11	1351.4	21.9	8.5	1.81	1206.7	11.8	12.0	1.15	15.93	46215	30	8	W
T	9	2218.6	6.0	5.0	1.35	1825.1	13.2	17.5	4.73	1594.8	24.0	16.0	4.52	1420.6	16.0	19.0	2.11	1351.8	21.9	8.5	1.82	1206.7	11.8	12.0	1.15	15.67	46243	28	9	T
F	10	2218.6	6.0	5.0	1.35	1825.0	13.3	16.5	4.46	1594.8	23.2	16.0	4.53	1420.5	16.0	19.0	2.11	1352.1	21.8	8.5	1.82	1206.6	11.6	12.0	1.15	15.41	46271	28	10	F
	11	2218.6	6.0	5.0	1.35	1825.0	13.7	16.0	4.33	1594.9	22.4	14.0	3.97	1420.7	14.4	6.5	0.74	1352.2	13.1	8.5	1.82	1206.6	11.6	12.0	1.15	13.36	46309	38	11	
	12	2218.6	6.0	5.0	1.35	1825.0	14.2	16.0	4.33	1595.0	21.7	12.0	3.41	1421.0	12.4	4.5	0.52	1352.2	9.1	8.5	1.83	1206.6	11.6	12.0	1.15	12.58	46342	33	12	
M	13	2218.7	6.0	5.0	1.35	1825.0	14.7	16.0	4.33	1595.0	21.5	20.5	5.77	1420.8	18.8	23.5	2.60	1352.5	20.8	8.5	1.83	1206.5	11.6	12.0	1.14	17.02	46356	14	13	M
T	14	2218.7	6.0	5.0	1.35	1825.0	15.3	16.0	4.33	1595.0	21.5	20.5	5.77	1420.7	20.5	23.5	2.60	1352.9	24.4	9.0	1.94	1206.5	11.6	12.0	1.14	17.13	46381	25	14	T
W	15	2218.7	6.0	5.0	1.35	1825.0	15.8	16.0	4.33	1595.0	21.7	20.5	5.78	1420.6	20.5	23.5	2.59	1353.3	26.2	9.0	1.94	1206.5	11.8	12.0	1.14	17.13	46412	31	15	W
T	16	2218.7	6.0	5.0	1.35	1825.0	16.3	16.0	4.33	1595.0	21.8	20.5	5.78	1420.5	20.5	23.5	2.59	1353.7	26.2	10.0	2.16	1206.5	12.0	12.0	1.14	17.35	46444	32	16	T
F	17	2218.7	6.0	5.0	1.35	1825.0	17.6	16.0	4.33	1595.0	22.0	20.5	5.78	1420.4	20.5	23.5	2.59	1354.0	26.2	12.5	2.70	1206.5	12.6	12.0	1.14	17.88	46473	29	17	F
	18	2218.7	6.0	5.0	1.35	1825.0	19.1	16.0	4.33	1595.0	22.2	18.5	5.23	1420.7	18.9	10.5	1.19	1354.0	17.1	15.5	3.34	1206.4	14.1	15.0	1.42	16.85	46506	33	18	
	19	2218.7	6.0	5.0	1.35	1825.1	20.7	16.0	4.33	1595.1	22.6	16.5	4.67	1421.0	16.9	8.5	0.97	1353.9	13.1	18.5	3.97	1206.3	16.6	18.0	1.69	16.98	46532	26	19	
M	20	2218.7	6.0	5.0	1.35	1825.1	22.2	16.0	4.33	1595.1	23.0	22.0	6.19	1420.9	20.9	25.0	2.76	1354.0	22.9	20.5	4.38	1206.2	19.5	21.0	1.96	20.97	46542	10	20	M
T	21	2218.7	6.0	5.0	1.35	1825.2	23.4	16.0	4.33	1595.1	23.4	22.0	6.19	1420.7	22.0	25.0	2.76	1354.1	26.0	21.0	4.49	1206.0	22.0	24.0	2.01	21.13	46558	16	21	T
W	22	2218.7	6.0	5.0	1.35	1825.2	23.5	16.0	4.33	1595.1	23.8	22.0	6.19	1420.6	22.0	25.0	2.75	1354.2	27.6	21.5	4.60	1206.0	23.4	24.0	2.01	21.23	46583	25	22	W
T	23	2218.8	6.0	5.0	1.35	1825.3	23.6	16.0	4.34	1595.1	23.7	22.0	6.19	1420.5	22.0	25.0	2.75	1354.4	27.6	21.0	4.50	1206.0	24.2	24.0	2.00	21.13	46612	29	23	T
F	24	2218.8	6.0	5.0	1.35	1825.3	23.7	16.0	4.34	1595.1	23.4	22.0	6.19	1420.4	22.0	25.0	2.75	1354.5	27.6	21.0	4.50	1206.0	24.2	24.0	2.01	21.13	46638	26	24	F
	25	2218.8	6.0	5.0	1.35	1825.4	23.8	16.0	4.34	1595.2	23.2	20.0	5.64	1420.7	20.4	12.0	1.35	1354.5	18.5	20.5	4.40	1206.0	24.2	24.0	2.01	19.09	46673	35	25	

Project:
 24EL Midnight Elevation (NGVD29)
 24ID Daily Average Inflow (kcfs)
 24OD Daily Average Release (kcfs)
 24GE Daily Power Generation (1000 MWh)

System:
 GE Daily Power Generation (1000 MWh)
 SG Midnight Storage (kaf)
 DSG Daily Storage Change (kaf)

Units:
 kcfs thousand cubic feet per second
 MWh megawatt hour
 kaf thousand acre-feet

The midnight elevation (24EL) will be shown in color when a reservoir enters one of the following zones.
1234.5 Exclusive Flood Control Zone (24EL)
1234.5 Surcharge Zone (24EL)

The daily average release (24OD) will be shown in color when a project's releases exceed the available power plant capacity.
34.5